

| DESCRIPTION | Water based, acrylic copolymer based, flat (eggshell) paint, optimized luminance and chrominance designed for green screen cyclorama with excellent adhesion on various type of surfaces; wood, various metals, concrete, plaster, old painted surfaces with water-based decorative primers/silicone free decorative topcoat paints and some plastics. | | | | | | | | | | | | | | | | |
|----------------------------------|--|--|---------------|-------|-----------|-----------------|------------|------------------|------------|----------------|-----------|---------------|-----------|---------------------|----------|---------|------------|
| APPLICATION AREA | Video and film productions | | | | | | | | | | | | | | | | |
| PRODUCT CODE | CL60111 | | | | | | | | | | | | | | | | |
| COLOR | Cyclorama Green | | | | | | | | | | | | | | | | |
| APPLICATION INSTRUCTIONS | Before application, ensure that all surfaces to be painted are clean, dry and dust free. If Cyclorama Green Basecoat Paint is applied as the first layer, there is no need to apply a primer. After basecoat paint is applied, applying two coats of Cyclorama Green Topcoat Paint depending on the substrate and surface quality is recommended for the maximum chroma and best result. Make sure to allow enough drying time for the basecoat paint before applying Cyclorama Green Topcoat Paint. Apply two coats of topcoat by roller/brush allowing minimum 2 hours between successive coats. If Cyclorama Green Basecoat Paint is not used, it is recommended to apply at least 2 or more Cyclorama Green Topcoat Paint. | | | | | | | | | | | | | | | | |
| COVERAGE | Approx. 215 sq ft/gal (5.3 m ² /lt), 75 microns dry film thickness | | | | | | | | | | | | | | | | |
| DRYING | Approx. 2-4 hours, 75 microns dry film, depending on temperature, humidity, and air ventilation. | | | | | | | | | | | | | | | | |
| VOC | < 60 gr/lt | | | | | | | | | | | | | | | | |
| CLEANING | Clean the application equipment with water. | | | | | | | | | | | | | | | | |
| SHELF LIFE | 12 months in original, closed containers at 41 – 95°F (5 – 35°C). Protect from frost and direct sunlight. | | | | | | | | | | | | | | | | |
| CONTENTS | <table><thead><tr><th></th><th><u>CAS NO</u></th></tr></thead><tbody><tr><td>Water</td><td>7737-18-5</td></tr><tr><td>Acrylic Polymer</td><td>25067-01-0</td></tr><tr><td>TiO₂</td><td>13463-67-7</td></tr><tr><td>Pigment Yellow</td><td>6486-23-3</td></tr><tr><td>Pigment Green</td><td>1328-53-6</td></tr><tr><td>Monoethylene Glycol</td><td>107-21-1</td></tr><tr><td>Texanol</td><td>25265-77-4</td></tr></tbody></table> | | <u>CAS NO</u> | Water | 7737-18-5 | Acrylic Polymer | 25067-01-0 | TiO ₂ | 13463-67-7 | Pigment Yellow | 6486-23-3 | Pigment Green | 1328-53-6 | Monoethylene Glycol | 107-21-1 | Texanol | 25265-77-4 |
| | <u>CAS NO</u> | | | | | | | | | | | | | | | | |
| Water | 7737-18-5 | | | | | | | | | | | | | | | | |
| Acrylic Polymer | 25067-01-0 | | | | | | | | | | | | | | | | |
| TiO ₂ | 13463-67-7 | | | | | | | | | | | | | | | | |
| Pigment Yellow | 6486-23-3 | | | | | | | | | | | | | | | | |
| Pigment Green | 1328-53-6 | | | | | | | | | | | | | | | | |
| Monoethylene Glycol | 107-21-1 | | | | | | | | | | | | | | | | |
| Texanol | 25265-77-4 | | | | | | | | | | | | | | | | |
| HAZARD STATEMENTS | H317 – May cause allergic skin reaction | | | | | | | | | | | | | | | | |
| WARNING | If you scrape, sand, or remove old paint you may release lead dust which may cause serious illness. | | | | | | | | | | | | | | | | |
| PRECAUTIONARY STATEMENTS: | | | | | | | | | | | | | | | | | |
| P101 | If medical advice is needed; have product container label in hand | | | | | | | | | | | | | | | | |

| | |
|------|---|
| P102 | Keep out of reach of children |
| P233 | Keep container tightly closed |
| P260 | Do not breathe dust/fume/gas/mist/vapors/spray |
| P262 | Do not get in eyes, on skin or on clothing. |
| P263 | Avoid contact during pregnancy and while nursing |
| P270 | Do not eat, drink, or smoke when using this product. |
| P312 | Call a poison center or a doctor / physician if you feel unwell. |
| P501 | Dispose the contents and containers in accordance with all local, regional, national, or international regulations. |

Treatments such as sanding, burning off etc. of dry paint films may generate hazardous dust and/or fumes.

Work in well ventilated areas. Use suitable protective equipment as necessary.

TDS and SDS are available on request.

LEAD AND MERCURY FREE.



DANGER: Contains TiO_2 , whose dust and spray may cause respiratory, skin and eye irritation when inhaled. May cause cancer.

Protect from direct sunlight



Protect from Frost $<0^\circ\text{C}$



Clean the surface



Add water if needed



Stir



$^\circ\text{C}$

Application Temperature:
41 – 95°F (5 – 35°C)