

CHROMALIGHT
TECHNICAL DATA SHEET
STUDIO BACKGROUND PAINT - WHITE

Rev. 2025/01
 Date. 02/07/2025

DESCRIPTION	High-performance, acrylic copolymer-based white paint with a flat finish. Offers exceptional hiding power and coverage in two coats. Self-priming with excellent adhesion to a variety of surfaces, including; wood, various metals, concrete, plaster, old painted surfaces with water-based decorative primers/silicone free decorative topcoat paints, PVC and select plastics.	
APPLICATION AREA	Video and Film Productions	
PRODUCT CODE	CL90015	
COLOR	Cyclorama White	
APPLICATION INSTRUCTIONS	Before application, ensure that all surfaces to be painted are clean, dry and dust free. Two coats of Chromalight Studio Background Paint - White is recommended depending on the substrate. Stir well and dilute with approx. 2% of water. Apply minimum of 2 coats by roller or brush, allowing 2 hours between coats, to reach 50-80 microns dry film. Close the paint container tightly after application.	
COVERAGE	Approx. 410 sq ft/gal (10 m ² /L) at 60 microns dry film thickness (single coat).	
DRYING	Approx. 2-4 hours, 60 microns dry film, depending on temperature, humidity, and air ventilation.	
VOC	< 40 gr/L	
CLEANING	Clean the application equipment with water.	
SHELF LIFE	12 months in original, closed containers at 41 – 95°F (5 – 35°C). Protect from frost and direct sunlight.	
CONTENTS	<u>CAS NO</u>	
	Water	7737-18-5
	Acrylic Polymer	25067-01-0
	TiO ₂	13463-67-7
	Monoethylene Glycol	107-21-1
	Texanol	25265-77-4
HAZARD STATEMENTS	H317 – May cause allergic skin reaction	
WARNING	If you scrape, sand, or remove old paint you may release dust which may cause serious illness.	

PRECAUTIONARY STATEMENTS:

P101	If medical advice is needed; have product container label in hand
P102	Keep out of reach of children
P233	Keep container tightly closed
P260	Do not breathe dust/fume/gas/mist/vapors/spray
P262	Do not get in eyes, on skin or on clothing.
P263	Avoid contact during pregnancy and while nursing
P270	Do not eat, drink, or smoke when using this product.
P312	Call a poison center or a doctor / physician if you feel unwell.
P501	Dispose the contents and containers in accordance with all local, regional, national, or international regulations.

Treatments such as sanding, burning off etc. of dry paint films may generate hazardous dust and/or fumes.

Work in well ventilated areas. Use suitable protective equipment as necessary.

TDS and SDS are available on request.

LEAD AND MERCURY FREE.




DANGER: Contains TiO_2 , whose dust and spray may cause respiratory, skin and eye irritation when inhaled. May cause cancer.

Protect from direct sunlight



Protect from Frost $<0^\circ\text{C}$




Clean the surface



Add water if needed



Stir



$^\circ\text{C}$

**Application
Temperature: 41 – 95°F
(5 – 35°C)**